

96G0HX-501

## OUTLINE

## OUTLINE OF CONSTRUCTION

1. The basic construction is the same as that of the previous model, however, some specifications are changed for improved reliability.
2. Rubber dampers replace the torsion springs of the clutch disc for improved dampening and reduction of vibration during acceleration and deceleration for F8, FE and FE DOHC engine models.

96G0HX-502

## SPECIFICATIONS

| Item                |                      |                        |                    | Engine                    | F8                            | FE                  | FE DOHC               | F2                  | RF |
|---------------------|----------------------|------------------------|--------------------|---------------------------|-------------------------------|---------------------|-----------------------|---------------------|----|
| Clutch control type |                      |                        |                    |                           | Hydraulic                     |                     |                       |                     |    |
| Clutch cover type   |                      |                        |                    |                           | Diaphragm spring              |                     |                       |                     |    |
| Clutch disc         | Set load             | N (kg, lb)             | General            | —                         | 4,316<br>(440, 968)           | —                   |                       | 4,022<br>(410, 902) |    |
|                     |                      |                        | ECE (Except UK)    | 4,022<br>(410, 902)       | 4,316 (440, 968)              |                     | 4,611<br>(470, 1,034) | 4,022<br>(410, 902) |    |
|                     |                      |                        | UK                 | 3,846<br>(392, 862)       | 4,316 (440, 968)              |                     | —                     | 3,846<br>(392, 862) |    |
|                     |                      |                        | Australia          | —                         |                               | 4,316<br>(440, 968) | —                     |                     |    |
|                     | Outer diameter       |                        |                    | mm (in)                   | 215 (8.465)                   | 225 (8.858)         |                       |                     |    |
|                     | Inner diameter       |                        |                    | mm (in)                   | 150 (5.906)                   |                     |                       |                     |    |
|                     | Thickness<br>mm (in) | Pressure<br>plate side | General            | —                         | 4.1 (0.16)                    | —                   |                       | 4.1 (0.16)          |    |
|                     |                      |                        | ECE<br>(Except UK) | 3.8 (0.15)                |                               |                     |                       |                     |    |
|                     |                      |                        | UK                 | 4.1 (0.16)                |                               | —                   | 4.1 (0.16)            |                     |    |
|                     |                      |                        | Australia          | —                         |                               | 4.1 (0.16)          | —                     |                     |    |
|                     | Flywheel side        |                        |                    | 3.5 (0.14)                |                               |                     |                       |                     |    |
| Clutch<br>pedal     | Type                 |                        |                    | Suspended                 |                               |                     |                       |                     |    |
|                     | Pedal ratio          | LHD                    |                    | 6.00 : 1                  |                               |                     |                       |                     |    |
|                     |                      | RHD                    |                    | 5.96 : 1                  |                               |                     |                       |                     |    |
|                     | Full stroke          |                        |                    | mm (in)                   | 135 (5.31)                    |                     |                       |                     |    |
| Height              |                      |                        | mm (in)            | 216.5—221.5 (8.524—8.720) |                               |                     |                       |                     |    |
| Master cylinder     |                      | Inner diameter         | mm (in)            | 15.87 (0.625)             |                               |                     |                       |                     |    |
| Release cylinder    |                      | Inner diameter         | mm (in)            | 19.05 (0.750)             |                               |                     |                       |                     |    |
| Clutch fluid type   |                      |                        |                    |                           | SAE J1703 or FMVSS 116, DOT-3 |                     |                       |                     |    |

Changed from previous model.

96G0HX-503