

WHEELS AND TIRES

OUTLINE	Q-2
SPECIFICATIONS.....	Q-2

96G0QX-501

OUTLINE

- The front tire pressure is increased from 196 kPa (2.0 kg/cm², 28 psi) to 216 kPa (2.2 kg/cm², 32 psi) on European models.

96G0QX-502

SPECIFICATIONS

Item			Standard tire and wheel			Temporary spare tire and wheel (If equipped)
			Europe, UK, Switz	Australia	New Zealand LHD and RHD General	
Wheels	Size		14x5 1/2-JJ, 15 x 6-JJ	14 x 5 1/2-JJ		4T x 15
	Offset mm (in)		42 (1.65)			53 (2.09)
	Diameter of pitch circle mm (in)		114.3 (4.5)			
	Material		Steel or aluminum alloy			Steel
Tires	Size		185/70HR14 185/70R14 87H 185/70R14 88H 195/70R15 86H	185/70HR14 185/70R14 87H		T125/70D15
	Air pressure kPa (kg/cm ² , psi)	Front	216 (2.2, 32)...up to 5 passengers 216 (2.2, 32)...full load	196 (2.0, 28)...up to 5 passengers 206 (2.1, 30)...full load		412 (4.2, 60)
		Rear	196 (2.0, 28)...up to 5 passengers 235 (2.4, 35)...full load	196 (2.0, 28)...up to 5 passengers 240 (2.4, 34)...full load		412 (4.2, 60)

96G0QX-503